

Simple Solutions Distributing LLC.

Makers Of *Wolverine Brand* Activated Carbon Filters

Simple Solutions Distributing
6 Jacobs Rd.
West Milford, NJ 07480

1-866-No-Stink (1-866-667-8465-Outside NJ)
1-973-846-7817 (inside NJ and Outside of the US)
E-Mail SimpleSolution1@optonline.net

Data Sheet: Super Wolverine vent odor filter Part # SWV



Shown with optional Saturation Indicator and Flange Coupling

Application: Atmospheric Vents/Low Flow Vents.
Overall Length: 11.5 Inches
Overall Height: 7 Inches
Installed Height: 4 Inches
Standard Inlet sizes: 3" to 6" Socket; ASTM D 2661
Optional couplings: 3" to 6" Van Stone Flange
Max CFM: 10 CFM
Carbon Capacity: 10LBS/.4 cubic feet *
Carbon Type: Catalytic
H2S Breakthrough Capacity gH2S/cc carbon; .15 (Min) ASTM D 6646

* The low apparent density of catalytic carbons means fewer pounds must be purchased to fill the required volume. Since H2S removal Capacity is based on bed volume, this results in direct cost savings.

Sulfursorb Catalytic Carbon Life Estimates							
Carbon Life Estimate based on constant flow at 5 PPM H2S Concentration							
CFM	1CFM	5CFM	10CFM	20CFM	30CFM	40CFM	50 CFM
Carbon Bed Contact Time-Seconds	24	4.8	2.4	1.2	.8	.6	.48
Carbon Life Days	5472.15	1459.24	547.22	273.61	182.41	136.80	109.44
Carbon Life Hours	131331.7	35021.79	13133.17	6566.58	4377.72	3283.29	2626.63
Carbon Life Estimate based on constant flow at 10 PPM H2S Concentration							
CFM	1CFM	5CFM	10CFM	20CFM	30CFM	40CFM	50 CFM
Carbon Bed Contact Time	24	4.8	2.4	1.2	.8	.6	.48
Carbon Life Days	2736.08	547.22	273.61	136.80	91.2	68.4	54.72
Carbon Life Hours	65665.85	13133.17	6566.58	3283.29	2188.86	1641.65	1313.32
Carbon Life Estimate based on constant flow at 20 PPM H2S Concentration							
CFM	1CFM	5CFM	10CFM	20CFM	30CFM	40CFM	50 CFM
Carbon Bed Contact Time	24	4.8	2.4	1.2	.8	.6	.48
Carbon Life Days	1368.04	273.61	136.80	68.40	45.60	34.20	27.36
Carbon Life Hours	32832.92	6566.58	3283.29	1641.65	1094.43	820.82	656.66
Carbon Life Estimate based on constant flow at 30 PPM H2S Concentration							
CFM	1CFM	5CFM	10CFM	20CFM	30CFM	40CFM	50 CFM
Carbon Bed Contact Time	24	4.8	2.4	1.2	.8	.6	.48
Carbon Life Days	912.03	182.41	91.20	45.60	30.40	22.80	18.24
Carbon Life Hours	21888.62	4377.72	2188.86	1094.43	729.62	547.22	437.77